

## Performance evaluation of Alternate fuels of diesel blended with Rubber seed oil and Mesquite Beans oil

<sup>1</sup>S.Ramasubramanian, <sup>2</sup>C.Gnanavel, <sup>3</sup>R. Sridhar, <sup>4</sup>K.Karunakaran

<sup>1</sup>Asst. Professor, Department of Automobile Engineering, VISTAS, Chennai, India

<sup>2,3,4</sup>Asst. Professor, Department of Mechanical Engineering, VISTAS, Chennai, India

<sup>1</sup>raams87@gmail.com

### Abstract

The consumption of diesel fuels increases day by day rapidly. This research focuses the experimental study of using the diesel fuel with natural oil as bio fuel. Carefully prepared ten different bio fuels are considered with pure diesel to optimize the use of diesel with natural oils. The fuels are tested in a naturally aspirated Kirloskar make single cylinder four-stroke compression ignition engine from no load to full load conditions. The ten different blended diesels prepared with Rubber seed oil, Mesquite Bean oil. Apart from pure diesel, the diesel blends with three different proportions with each of Mesquite Beans oil and, Rubber seed oil. The results are discussed and best bio fuel is suggested.

**Key Words:** Rubber seed oil, Mesquite Beans oil, Diesel, Bio-diesel, Fuel consumption, BHP

### 1. Introduction

Research on use of non-renewable fossil fuels is must to meet global energy the demand. The supply of fossil fuels is getting reduced and price hike of them is increased day by day. This simulates the researchers to search the alternate fuels to make up the supply and meeting the fast growing energy demand globally. Biodiesel is one of the option and plausible supplement for conventional diesel demand. [1]The biodiesel from the vegetable oil (which use for food preparation) increase the cost of food and biodiesel, [2]If the blend proportion in diesel increases the total fuel consumption will be increased, [3]emission of CO<sub>2</sub> and HC will be decreased and NO<sub>x</sub> emission increased. [4]The use of biodiesel may cause problem in long term but initially none and does not need to modify the engine, [5] reported that biodiesel of rubber seed oil meet the bio-auto fuel EN 14214 standard and compared its thermal stability with petrol and diesel through thermo-gravimetric analysis and highlighted such fuel source in Thailand, [6] also ensured that rubber seed oil based biodiesel fulfilled the bio-auto fuel ASTM D6751 and EN14214, [7] reported as sub-Saharan Africa (SSA) countries has capacity of 166.91MT of biodiesel production from the estimated 179.47MT of rubber seeds, such countries have an attractive choice for the sustainable development, [8] estimated the potential of such oil production at Southeast Asiaas1.80 Mt from the estimated rubber seeds of 1.94 Mt,[9] optimized the parameters using Response surface methodology in esterification process of rubber seed oil, [10] Mesquite trees are unique kind, abundantly available which offers non-edible organic products, [11] They emit CO<sub>2</sub> spoil the agriculture land and Nowadays researchers reported that primary food source for caravans and settlers, at 1841 suffering men used beans of Mesquite and termed as “manna from heaven, [12]usedCarboxymethyl cellulose pulp which derived from mesquite tree, as nano-composite material for preparing CMC/Fe<sub>3</sub>O<sub>4</sub>nano-composite material,.

### 2. Materials and Methods

#### 2.1 Biodiesel Preparation

The preparation include to maintain the viscosity (reduce if it is high) to suit for the fuel for IC engine. Transesterification process employed for biodiesel preparation which is the reaction of vegetable oil or fat or oil in

presence of alkaline, acidic with alcohol to form the glycerol and biodiesel. Here methanol used as alcohol. Initially the oils are filtered for removing solid impurities and heated up to 100°C and maintain for 30 minutes to remove the moisture presence. The first stage is called stageesterification and the second stage is referred as Transesterification process. In the first stage the free fatty acid content in oil is removed by heated up the oil at 60-65°C for 60 minutes in magnetic stirrer with pure methanol and pure acid catalyst. Then water wash of oil is done in separating funnel. The hot water of same oil temperature added in the separating flask for washing out the dust, sulphur and carbon contents. The esterified oil is taken for transesterification process. The 1% by weight of solid catalyst of 4g Sodium hydroxide dissolved in 130 ml of methanol then the same added in esterified oil of 1000 ml at the temperature of 60°C for 60 minutes. After completing of reaction, the mixture is allowed to settle for more than 10 hours in the separating flask. In the settled flask bottom layer of the mixture contains glycerin, excess alcohol, catalyst impurities and traces of un-reacted oil. The coarse biodiesel floats at the top. Again the mixture heated above 100°C and maintained for 10 to 15 minutes to separate coarse biodiesel. The impurities were cleaned by washing two to three times with 100ml water. Now the biodiesel is ready for use in CI engine for investigation.

### 2.2 Blending with the diesel

After successful completion of the transesterification process, such vegetable oils can use for CI Engine fuel either in pure form or blends of diesel. Here both cases are considered for evaluation. Some of the merits like no need of engine modification, minimizing the cold weather effects, and particulate emission reduction and improve the capability and solvency, can be get by blending the vegetable oil with diesel. For blending the oils with diesel blender equipment is used. The blender equipment has reactor, heater with thermostat control and mechanical stirrer and separately a glass separator. The preferred blending ratios are: 30%, 40% and 50%.

### 2.3 Blend Properties

It is important to know the properties of blends before test in the Engine. The addition of biodiesel to diesel may affect some key properties like viscosity, lubricity, blend stability and energy content.

#### Experimental Setup:

Thenaturally aspirated Kirloskar make,single cylinder four-stroke compression ignition engine is considered for testing the alternate fuels. The Eddy current Dynamometer used to add the load from 20% to 100% with step of 20%. The sensors provided for measuring various temperatures. The engine specifications furnished in Table 1. The experimental set up consists of smoke meter to evaluate the emission.

Table 1 Experimental setup

Description	Specification
Engine model	Kirloskar TV 1 model
Compression ratio	5:1-23:1
Fuel	Diesel
Engine type	Vertical, 4 stroke cycle, single acting, High Speed, Diesel Engine
Number of cylinders	Single
Bore &Stroke (mm)	80*110
Cubic Capacity	0.553 liters
Rated shaft speed	1500 rpm
Compression ratio	16.5 .1
Starting	Crank(manually)

Dynamometer	Eddy current
Combustion	Direct injection
Governing	Class "B1"
Power Rating	5 HP
Cooling system	Water cooled
Type of load	Electrical load

### 3. Experimentation

The load test and emission test were conducted. The appropriate fuel filled in the fuel tank. The engine oil level, cooling water flow, no load conditions were ensured then start the engine manually. After reach of rated speed of 1500 rpm, the dynamometer, analysers and measuring meters switched on. The load of 20%, 40%, 60%, 80% and 100% were set by the ampere rating as 3,5,7,9 and 11Amps. The engine speed adjusted to 1500 rpm by increasing the acceleration on every loading. The required parameters (quantity of air consumed, fuel consumed, temperatures of cooling water at inlet and outlet, exhaust air temperature, etc) observed for heat balance and load test for computing the total fuel consumption, specific fuel consumption, indicated power, frictional power, break power, indicated thermal efficiency, break thermal efficiency and mechanical efficiency. The alternate fuel performance with the engine was furnished in terms of TFC, SFC, IP, BP, FP,  $\eta_{ith}$ ,  $\eta_{bth}$  and  $\eta_{mech}$ . For emission test, the smoke, hydrocarbons and carbon monoxide were observed and such a way the diesel, biodiesel and their blends with various proportions were investigated.

### 4. Results and Discussions

The fuels like pure diesel, blended diesel of Mesquite bean oil of contents 30%, 40% and 50%, blended diesel of cotton seed oil of contents 30%, 40% and 50%, preheated soybean oil of content 30% at preheating temperatures like 50, 60, 70 and 80 degree centigrade are used separately from no load condition to full load condition. The performance of these fuels presented in the graphical form.

The figure 1 illustrates the performance relationship with Brake Power and specific fuel consumptions. The pure diesel needs low specific fuel consumption at all load conditions than other blended diesels considered in this study. B30 RSO needs lighter higher specific fuel consumption at all conditions when compare to Pure diesel but other than B30 RSO that's required more SFC.

The figure 2 illustrates the performance relationship with Brake Power and total fuel consumptions. The pure diesel needs low total fuel consumption at all load conditions than other blended diesels considered in this study. B30 RSO needs lighter higher total fuel consumption at all conditions when compare to Pure diesel but other than B30 RSO that's required more TFC.

The figure 3 illustrates the performance relationship with Brake Power and Indicated power. The pure diesel needs low Indicated power at all load conditions than other blended diesels considered in this study. B30 RSO performs lighter higher Indicated power at all conditions when compare to Pure diesel but other than B30 RSO that's produce very High Indicated power.

The figure 4 illustrates the performance relationship with Brake Power and Brake Thermal Efficiency. The pure diesel needs high Brake Thermal efficiency at all load conditions than other blended diesels considered in this study. B30 RSO performs lighter lower Brake Thermal efficiency at all conditions when compare to Pure diesel but other than B30 RSO that's produce very low Brake Thermal Efficiency.

The figure 5 illustrates the performance relationship with Brake Power and Indicated Thermal Efficiency. The pure diesel needs low Indicated Thermal efficiency at all load conditions than other blended diesels considered in this study. B30 RSO performs lighter higher Indicated Thermal efficiency at all conditions when compare to Pure diesel but other than B30 RSO that's produce very High Indicated Thermal Efficiency.

The figure 6 illustrates the performance relationship with Brake Power and Mechanical Efficiency. The pure diesel needs high mechanical efficiency at all load conditions than other blended diesels considered in this study. B30 RSO performs lighter lower mechanical efficiency at all conditions when compare to Pure diesel but other than B30 RSO that's produce very low Mechanical Efficiency.




Figure 1.




Figure 2




Figure 3

Brake Power Vs Brake Thermal Efficiency




Figure 4

Brake Power Vs Indicated Thermal Efficiency




Figure 5  
Brake Power Vs Mechanical Efficiency




Figure 6

## 5. Conclusion

The diesel blended with rubber seed oil and mesquite bean oil in different proportion to form the six different kind of blended diesels for conventional use. The experiments were carried out successfully and discussed well. The Rubber Seed oil with 30% blend with diesel gave low total fuel consumption, high Mechanical Efficiency, high Indicated Thermal Efficiency, high Brake Thermal Efficiency, low specific fuel consumption and develop high Indicated power than other blended diesel but higher than the pure diesel. Hence the Rubber Seed oil with 30% blend with diesel is suggested.

## References

1. NabanitaBanerjee, RiticaRamakrishnana, Tushar Jasha, 'Biodiesel production from used vegetable oil collected from shops selling fritters in Kolkata,4th International Conference on Advances in Energy Research 2013, ICAER 2013, Volume 54 ( 2014 ) 161 – 165,
2. B.Bharath Kumar , M.Rajesh , K.Srinivas. "Performance and Emission Analysis of Flex Seed Oil Blended With Diesel Using Methyl Esters as Additive On VCR Engine", International Journal of Engineering Trends and Technology (IJETT), V17(3),103-108 Nov 2014.
3. Dipak Patil , Dr. Rachayya. Arakerimath "Performance characteristics and analysis of Jatropa oil in multicylinder turbocharge Compression Ignition Engine" International Journal of Engineering Research and Development, Volume 1, Issue 10 (June 2012), PP.50-55.
4. Shiv Lal, V. K. Gorana, N. L. Panwar, 'A Comparative Study of Thumba Seed Bio Diesel' Journal of Environmental Protection, 2011, 2, 454-459.

5. WuttichaiRoschat, TheeranunSiritanon, BoonyawanYoosuk, TaweesakSudyoadsuk and VinichPromarak, 'Rubber seed oil as potential non-edible feedstock for biodiesel production using heterogeneous catalyst in Thailand', *Renewable Energy*, Volume 101, February 2017, Pages 937-944.
6. Junaid Ahmad, SuzanaYusup, AwaisBokhari and Ruzaimah Nik Mohammad Kamil, 'Study of fuel properties of rubber seed oil based biodiesel', *Energy Conversion and Management*, Volume 78, February 2014, Pages 266-275.
7. Yixin Zhu, Jianchu Xu, Qiaohong Li and Peter E. Mortimer, 'Investigation of rubber seed yield in Xishuangbanna and estimation of rubber seed oil based biodiesel potential in Southeast Asia', *Energy*, Volume 69, 1 May 2014, Pages 837-842
8. Samuel E. Onoji, Sunny E. Iyuke, Anselm I. Igbafe and Diakanua B. Nkazi, 'Rubber seed oil: A potential renewable source of biodiesel for sustainable development in sub-Saharan Africa', *Energy Conversion and Management*, Volume 110, 15 February 2016, Pages 125-134.
9. Sumit H. Dhawane, Akash Pratim Bora, Tarkeshwar Kumar and Gopinath Halder, 'Parametric optimization of biodiesel synthesis from rubber seed oil using iron doped carbon catalyst by Taguchi approach', *Renewable Energy*, Volume 105, May 2017, Pages 616-624.
10. <https://www.desertusa.com/flora/mesquite-tree.html#ixzz5CJhrwrxp>
11. P. Solomon Durairaj, 'Experimental Analysis of Diesel Engine using Mesquite Oil', *International Journal of Modern Trends in Engineering and Research*, Volume 03, Issue 11, November – 2016, pages 31-42.
12. Ahmed Salama, Sanad Etri, Salah A.A. Mohamed and Mohamed El-Sakhawy, 'Carboxymethyl cellulose prepared from mesquite tree: New source for promising nanocomposite materials' *Carbohydrate Polymers*, Volume 189, 1 June 2018, Pages 138-144.